

## Standard Grounding Kit ,for cable 1/4"-7/8",1.0m

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Suitable for screen diameter of cable OD 1/4"-7/8"
- Operation Temperature -40~70 °C
- Waterproof IP68



### Product Classification

Material Number	6003119
Status	Active
Detail Description	Standard Grounding Kit,for cable 1/4"-7/8",1.0m,installation accessories including

### General Specifications

Bonding Conductor Material	Copper
Bonding Conductor Wire Size	AWG6
Grounding Strap Material	Copper,Tin Plated
Lug Type	One-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
PVC tape Material	PVC
Butyl Rubber Tape Material	Butyl

### Dimensions

Bonding Conductor Length	1.0m   39.3 in
Lug Hole Size	M8
Screw Size	M8x25

### Electrical Specifications

Contact Transition Resistance	Maximum 10mΩ
-------------------------------	--------------

### Packaging and Weights

Height, packed	180 mm   7.0 in
Width, packed	310 mm   12.2 in

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 23, 2023  
 Public

Length, packed	400 mm   15.75 in
Included	Grounding kit   M8x25 screw   M8 spring washer   M8 flat washer   M8 nut   One roll of 6m PVC tape   One roll of 0.6m butyl rubber Tape
UOM	1 Kit
Packaging	Bag
Weight, gross	0.367 kg   0.809 lb

---

**Certifications and Compliance**

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

