

## Standard Grounding Kit ,for cable 3/8",2.0m

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Suitable for screen diameter of cable OD 3/8"
- Operation Temperature -40~70 °C
- Waterproof IP68



### Product Classification

|                    |   |
|--------------------|---|
| Material Number    | 6004029   |
| Status             | Active  |
| Detail Description | Standard Grounding Kit,for cable 3/8",2.0m,installation accessories including |

### General Specifications

|                             |                   |
|-----------------------------|-------------------|
| Bonding Conductor Material  | Copper            |
| Bonding Conductor Wire Size | AWG10             |
| Grounding Strap Material    | Copper,Tin Plated |
| Lug Type                    | Two-hole lug      |
| Screw Material              | Stainless Steel   |
| Flat washer Material        | Stainless Steel   |
| Spring washer Material      | Stainless Steel   |
| Nut Material                | Stainless Steel   |
| PVC tape Material           | PVC               |
| Butyl Rubber Tape Material  | Butyl             |

### Dimensions

|                          |                |
|--------------------------|----------------|
| Bonding Conductor Length | 2.0m   78.7 in |
| Lug Hole Size            | M8             |
| Screw Size               | 3/8"x1"        |

### Electrical Specifications

|                               |              |
|-------------------------------|--------------|
| Contact Transition Resistance | Maximum 10mΩ |
|-------------------------------|--------------|

### Packaging and Weights

|                |                  |
|----------------|------------------|
| Height, packed | 180 mm   7.0 in  |
| Width, packed  | 310 mm   12.2 in |

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 23, 2023  
 Public

|                |   |
|----------------|---|
| Length, packed | 400 mm   15.75 in   |
| Included       | Grounding kit   3/8"x1" screw   3/8" spring washer   3/8" flat washer   3/8" nut   One roll of 6m PVC tape   One roll of 0.6m butyl rubber Tape |
| UOM            | 1 Kit   |
| Packaging      | Bag   |
| Weight, gross  | 0.382 kg   0.842 lb   |

---

### Certifications and Compliance

---

|               |  |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| ROHS          | Compliant  |

