-04-01 VERSION A/4 DATE 03/25/2023



Waveguide clamp, for R70 waveguide

- Easy and quick installation
- Robust design & material for outdoor use
- Universal fixing design on bracket, angle steel
- Operation Temperature -40~85 ℃
- RoHS certified



Product Classification	
Material Number	6001263
Part Number	-
Status	Active
Detail Description	Waveguide cable clamp, for R70 waveguide
General Specifications	
Metal Parts Material	Stainless steel 304
Rubber Parts Material	EPDM
Mounting Plate Thickness	3-25mm
Dimensions	
Threaded Rod Length	400 mm 15.75 in
Adapter Width	24 mm 0.94 in
Rubber Lining Hole	45 mm X 25 mm
Waveguide Size	R70 WR137 WG14
Environmental Specifications	
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
UV Resistance	ASTM G155, 720 hours
Salt Spray	ASTM B117, 72 hours
Packaging and Weights	
Width, packed	600 mm 23.62 in
Length, packed	150 mm 5.91 in
Included	Angle adapter M8 spring washer M8 nut M8 threaded rod Rubber lining Clamp
UOM	Pcs
Packaging	Bag

For more information, please visit: www.maxdao.com



Public

Page 1 of 2







Weight, gross	0.495 kg 1.091 lb
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant



For more information, please visit: