

## Hoisting Grip, Pre-Laced, Non-metallic, for 3/8 in Cable

- Hoisting grips are Made of (Kevlar)Fiber Aramid, High strength during supporting cables.
- Closed mesh for when end of cable is available.
- No rusting worries, no-metallic will not interfere with signal transmission.
- Plastic coating protects the aramid from UV, ensuring stable performance of the aramid.
- CE certified




---

### Product Classification

Material Number	6003501
Part Number	-
Detail Description	Hoisting Grip, Pre-Laced, Non-metallic, for 3/8 in Cable

---

### Details

Cable Range	0.40-0.47 in   10.1-11.9 mm
Mesh Length	23.6 in   600.0 mm
Eye Length	6.0 in   152.4mm
Maximum Spacing Intervals	200 ft   60.96 m
Approximate Break Strength	800 lbs   363 kg
Working Load	160 lbs   72.6 kg (Safety Factor 5*)
Mesh Material	Aramid Fiber
Warning Label	Yellow Mylar

---

### Packaging and Weights

UOM	1 pcs
Packaging	Bag
Weight, gross	0.14 lb   0.06 kg

---

### Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
CE	Compliant