## MAXDAO

## Grounding Kit, Hinge Type, 1/2", 0.6 Meter

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation Temperature -40~70 °C
- Waterproof IP67



Product Classification	
Item Number	6004545
Part Number	-
Detail Description	Grounding kit, hinge type, for 1/2" cable, 0.6 Meter installation accessories including
General Specifications	
Bonding Conductor Material	Copper, Tin Plated
Bonding Conductor Wire Size	AWG6
Grounding Strap Material	Copper, Tin Plated
Lug Type	One-hole lug
Hinge Material	Stainless Steel
Rubber Material	EPDM
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
Dimensions	
Bonding Conductor Length	0.6 m   2 feet
Lug Hole Size	M8
Screw Size	M8x20 mm
Suitable Cable	1/2"
Environmental Specifications	
Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Electrical Specifications	
Contact Transition Resistance	Maximum 10mΩ
Packaging and Weights	
Height, Packed	200 mm   7.87 in

For more information, please visit: www.maxdao.com

 $\boxtimes$ 

(in

## ©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 21, 2024 Public

MAXDAO

Width, Packed	200 mm   7.87 in
Included	Grounding kit   Hardware
UOM	Kit
Packaging	Bag
Weight, Gross	0.245 kg   0.540 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

Page 2 of 2

For more information, please visit: www.maxdao.com

Î  $\boxtimes$ 

©Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 21, 2024 Public