

## Heat Shrink Tube, Dual Wall, $\phi$ 12.7mm, White

- High resistance to impact and abrasion
- Adhesive lined
- Shrink ratio: 3:1
- Continuous operating temperature: -45°C to 125°C
- Shrink temperature: 120°C min



### Product Classification

Item Number	6004659
Part Number	-
Detail Description	Heat Shrink Tube, dual wall, $\phi$ 12.7mm, white

### General Specifications

Material	PE
Color	White
Cable Range	$\phi$ 4.8-12.5 mm   0.38-0.49 in
Adhesive(Y/N)	Y
Shrink Ratio	3:1

### Dimensions

Expanded Inside Diameter, minimum	12.7 mm   0.50 in
Recovered Inside Diameter, maximum	4.2 mm   0.165 in
Total Recovered Wall Thickness	1.65 mm   0.065 in

### Environmental Specifications

Operating Temperature	-45 °C to +125 °C (-49 °F to +257 °F)
Shrink Temperature Minimum	120 °C (248 °F)

### Electrical Specifications

Voltage	600 V
Dielectric Strength	$\geq$ 15 KV/mm

### Packaging and Weights

Roll diameter	500 mm   1.64 in
Roll height	34 mm   0.11 in
Meter per roll	25 m
UOM	1 Pcs

Packaging	Carton
Weight, Gross	1.21 kg   2.66 lbs
<b>Certifications and Compliance</b>	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant

