

Grounding Kit, Universal Type, 1/4"-1-5/8", 0.6 Meter, UL Grounding Cable

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation Temperature -40~70 °C
- Waterproof IP67

**Product Classification**

Item Number	6004782
Part Number	-
Detail Description	Grounding Kit, universal type, for 1/4"-1-5/8" cable, 0.6 Meter, installation accessories including

General Specifications

Bonding Conductor Material	Copper, Tin Plated
Bonding Conductor Wire Size	AWG6, UL1015
Grounding Strap Material	Copper, Tin Plated
Lug Type	One-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
PVC tape Material	PVC
Butyl Rubber Tape Material	Butyl

Dimensions

Bonding Conductor Length	0.6 m 2 feet
Lug Hole Size	M8
Screw Size	M8x25 mm
Suitable Cable	1/4"-1-5/8"

Environmental Specifications

Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Weatherproofing Method	Butyl and electric tape

Electrical Specifications

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 21, 2024
 Public

Contact Transition Resistance	Maximum 10mΩ
-------------------------------	--------------

Packaging and Weights

Height, Packed	320 mm 12.60 in
----------------	-------------------

Width, Packed	220 mm 8.66 in
---------------	------------------

Included	Grounding kit Hardware Lug One roll of PVC tape One roll of butyl rubber tape One Braided ground strap
----------	---

UOM	Kit
-----	-----

Packaging	Bag
-----------	-----

Weight, Gross	0.251 kg 0.553 lbs
---------------	----------------------

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
---------------	---

RoHS	Compliant
------	-----------

