

## Heavy Quick Install Round Member Adapter, 60A-150A, SS304

- Wider operating range
- For attaching to round members
- Good performance for outdoor



### Product Classification

Item Number	6005253
Part Number	-
Detail Description	Heavy quick install round member adapter, for 60-150mm round member, SS304

### General Specifications

Material	Stainless steel 304
Surface Treatment	Passivation and sealing
Color	Natural
Screw Type	Hexagon socket head, M6

### Dimensions

Band Width	19.0 mm   0.748 in
Band Thickness	0.8 mm   0.031 in
Size Range	60-150 mm   2.36"-5.91"

### Mechanical Specifications

Minimum Destructive Torque	110 kgf.cm-120 kgf.cm
----------------------------	-----------------------

### Environmental Specifications

Corrosion Resistance	≥720 hours in salt spray chamber, base on IEC 60068-2-11
----------------------	--

### Packaging and Weights

Height, Packed	250 mm   9.84 in
Width, Packed	310 mm   12.20 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.2 kg   0.44 lbs

### Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
---------------	--

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 23, 2024  
 Public

---

RoHS

Compliant

---

**For more information, please visit:**  
[www.maxdao.com](http://www.maxdao.com)



**©Maxdao Inc. All rights reserved.**

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 23, 2024

Public