

**Cable Breakout Boots, 2 Cores, 35/14mm, Black**

- Boots for 2 way cable breakouts
- Adhesive lined
- Shrink ratio: >2:1
- Continuous operating temperature: -55°C to 110°C
- Shrink temperature: 70°C min

**Product Classification**

Item Number	6005754
Part Number	-
Detail Description	Cable breakout boots, 2 cores, 35/14mm, black

**General Specifications**

Material	XLPO
Color	Black
Number Of Cores	2
Adhesive(Y/N)	Y
Shrink Ratio	>2:1

**Dimensions**

Expanded Boot Diameter	30 mm   1.18 in
Recovered Boot Diameter	14 mm   0.55 in
Expanded Core Diameter	12 mm   0.47 in
Recovered Core Diameter	4.3 mm   0.17 in
Total Recovered Length	93 mm   3.66 in
Core Recovered Length	23 mm   0.91 in
Recovered Wall Thickness	2.4 mm   0.09 in

**Environmental Specifications**

Operating Temperature	-55 °C to +110 °C (-67 °F to +230 °F)
Shrink Temperature Minimum	70 °C (94 °F)

**Electrical Specifications**

Voltage Maximum	1000 V
Dielectric Strength	≥15 KV/mm

**Packaging and Weights**

Height, Packed	500 mm   19.68 in
----------------	-------------------

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 8, 2024

Public

Width, Packed	300 mm   11.81 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.012 kg   0.026 lbs
<b>Certifications and Compliance</b>	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

