TEMPLATE# ITM0401 VERSION A/8 DATE 08/20/2024



Support Grip, Offset Eye, Closed Mesh, Non-metallic for 1.00-1.50 in Cable

- Made of (Kevlar)Fiber Aramid, High strength during supporting cables.
- Closed mesh support grips are used when the end of the cable is accessible
- No rusting worries, no-metallic will not interfere with signal transmission.
- The offset eye grip is designed to support the cable weight as it hangs vertically or horizontally.
- Plastic coating protects the Aramid from UV, ensuring stable performance of the Aramid.
- **CE** certified



Part Number - Support Grip, Offset Eye, Closed Mesh,Non-metallic for 1.00-1.50 in Cable Details Cable Range 1.00-1.50 in 25.4-38.1 mm Mesh Length 22.6 in 574.0 mm Eye Length 6.0 in 152.4 mm Approximate Break Strength 3500 lbs 1587 kg Working Load 350 lbs 1587 kg (Safety Factor 10*) Mesh Material Aramid Fiber Packaging and Weights UOM 1 pcs Packaging Bag Weight, gross 0.44 lb 0.20 kg Certifications and Compliance ISO 9001:2015 RoHS Compliant	Product Classification		
Detail Description Support Grip, Offset Eye, Closed Mesh,Non-metallic for 1.00-1.50 in Cable Details Cable Range 1.00-1.50 in 25.4-38.1 mm Mesh Length 22.6 in 574.0 mm Eye Length 6.0 in 152.4 mm Approximate Break Strength 3500 lbs 1587 kg Working Load 350 lbs 158.7 kg (Safety Factor 10*) Mesh Material Aramid Fiber Packaging and Weights UOM 1 pcs Packaging Bag Weight, gross 0.44 lb 0.20 kg Certifications and Compliance Designed, manufactured and/or distributed under this quality management system ROHS Compliant	Material Number	6006671	
Detail Description 1.00-1.50 in Cable Details Cable Range 1.00-1.50 in 25.4-38.1 mm Mesh Length 22.6 in 574.0 mm Eye Length Approximate Break Strength 3500 lbs 1587 kg Working Load 350 lbs 158.7 kg (Safety Factor 10*) Mesh Material Aramid Fiber Packaging and Weights UOM 1 pcs Packaging Bag Weight, gross 0.44 lb 0.20 kg Certifications and Compliance ISO 9001:2015 RoHS Compliant Compliant	Part Number	-	
Cable Range 1.00-1.50 in 25.4-38.1 mm Mesh Length 22.6 in 574.0 mm Eye Length 6.0 in 152.4 mm Approximate Break Strength 3500 lbs 1587 kg Working Load 350 lbs 158.7 kg (Safety Factor 10*) Mesh Material Aramid Fiber Packaging and Weights UOM 1 pcs Packaging Bag Weight, gross 0.44 lb 0.20 kg Certifications and Compliance ISO 9001:2015 RoHS Compliant	Detail Description	• • • • • • • • • • • • • • • • • • • •	
Mesh Length Eye Length Approximate Break Strength Approximate Break Strength Working Load Mesh Material Packaging and Weights UOM 1 pcs Packaging Weight, gross Certifications and Compliance ISO 9001:2015 ROHS 22.6 in 574.0 mm 6.0 in 152.4 mm As mid Fiber As mid Fiber Aramid Fiber Packaging Fiber Bag 0.44 lb 0.20 kg Designed, manufactured and/or distributed under this quality management system Compliant	Details		
Eye Length Approximate Break Strength Approximate Break Strength 3500 lbs 1587 kg Working Load 350 lbs 158.7 kg (Safety Factor 10*) Mesh Material Aramid Fiber Packaging and Weights UOM 1 pcs Packaging Bag Weight, gross 0.44 lb 0.20 kg Certifications and Compliance ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system Compliant	Cable Range	1.00-1.50 in 25.4-38.1 mm	
Approximate Break Strength 3500 lbs 1587 kg Working Load 350 lbs 158.7 kg (Safety Factor 10*) Mesh Material Aramid Fiber Packaging and Weights UOM 1 pcs Packaging Bag Weight, gross 0.44 lb 0.20 kg Certifications and Compliance ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system Compliant	Mesh Length	22.6 in 574.0 mm	
Working Load Mesh Material Aramid Fiber Packaging and Weights UOM 1 pcs Packaging Bag Weight, gross 0.44 lb 0.20 kg Certifications and Compliance ISO 9001:2015 Bosigned, manufactured and/or distributed under this quality management system Compliant	Eye Length	6.0 in 152.4 mm	
Mesh Material Aramid Fiber Packaging and Weights UOM 1 pcs Packaging Bag Weight, gross 0.44 lb 0.20 kg Certifications and Compliance ISO 9001:2015 RoHS Designed, manufactured and/or distributed under this quality management system Compliant	Approximate Break Strength	3500 lbs 1587 kg	
Packaging and Weights UOM 1 pcs Packaging Bag Weight, gross 0.44 lb 0.20 kg Certifications and Compliance ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system Compliant	Working Load	350 lbs 158.7 kg (Safety Factor 10*)	
UOM 1 pcs Packaging Bag Weight, gross 0.44 lb 0.20 kg Certifications and Compliance ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system Compliant	Mesh Material	Aramid Fiber	
Packaging Weight, gross 0.44 lb 0.20 kg Certifications and Compliance ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system Compliant	Packaging and Weights		
Weight, gross Certifications and Compliance ISO 9001:2015 RoHS Designed, manufactured and/or distributed under this quality management system Compliant	UOM	1 pcs	
Certifications and Compliance ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system Compliant	Packaging	Bag	
ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system Compliant	Weight, gross	0.44 lb 0.20 kg	
ROHS quality management system Compliant	Certifications and Compliance		
	ISO 9001:2015	_	
CE Compliant	RoHS	Compliant	
	CE	Compliant	



For more information, please visit:

