


Cable Breakout Boots, 2 Cores, 60/23mm, Black

- Boots for 2 way cable breakouts
- Adhesive lined
- Shrink ratio: >2:1
- Continuous operating temperature: -55°C to 110°C
- Shrink temperature: 70°C min



Product Classification

Item Number	6008234
Part Number	-
Detail Description	Cable breakout boots, 2 cores, 60/23mm, black

General Specifications

Material	XLPO
Color	Black
Number Of Cores	2
Adhesive(Y/N)	Y
Shrink Ratio	>2:1

Dimensions

Expanded Boot Diameter	60 mm 2.36 in
Recovered Boot Diameter	23 mm 0.90 in
Expanded Core Diameter	22.5 mm 0.88 in
Recovered Core Diameter	8 mm 0.32 in
Total Recovered Length	105 mm 4.13 in
Core Recovered Length	25 mm 0.98 in
Recovered Wall Thickness	2.4 mm 0.09 in

Environmental Specifications

Operating Temperature	-55 °C to +110 °C (-67 °F to +230 °F)
Shrink Temperature Minimum	70 °C (94 °F)

Electrical Specifications

Voltage Maximum	1000 V
Dielectric Strength	≥15 KV/mm

Packaging and Weights

Height, Packed	500 mm 19.68 in
----------------	-------------------

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 8, 2024
 Public

Width, Packed	300 mm 11.81 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.033 kg 0.072 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

