

## Cold Shrink Tube, $\phi$ 30x100mm, Grey

- Easy and quick installation
- Manufactured from silicone rubber
- Suitable for a wide range of cable sizes
- No special tools or training required for installation
- Offering good mechanical, insulation and sealing protection



### Product Classification

Item Number	6008385
Part Number	-
Detail Description	Cold shrink tube, $\phi$ 30x100mm, grey

### General Specifications

Material	Silicone
Cable type	Corrugated   Elliptical Waveguide   Smoothwall
Cable Range	$\phi$ 9-28 mm   0.36-1.10 in
Color	Grey
Mastic(Y/N)	N
Shrink Ratio	4:1

### Dimensions

Length Before Shrink	100 mm   3.93 in
Length After Shrink	120 mm   4.72 in
Inner Diameter Before Shrink(ID)	30 mm   1.18 in
Inner Diameter After Shrink(ID)	8 mm   0.31 in
Thickness After Shrink	3.1 mm   0.12 in

### Environmental Specifications

Operating Temperature	-60 °C to +90 °C (-76 °F to +194 °F)
Weatherproof Resistance	IP67, based on ISO20653:2013
UV Resistance	$\geq$ 1000 hours, base on ASTM G154-16

### Packaging and Weights

Height, Packed	150 mm   5.90 in
Width, Packed	50 mm   1.96 in

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 8, 2024  
 Public

UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.035 kg   0.077 lbs
<b>Certifications and Compliance</b>	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

