

## Feeder Cable Clamp, 10x7-9mm

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C
- Suitable for 7-9mm cable



| Product Classification              |                                                                                  |
|-------------------------------------|----------------------------------------------------------------------------------|
| Item Number                         | 6008441                                                                          |
| Part Number                         | -                                                                                |
| Detail Description                  | Feeder cable clamp, for 7-9mm cable, 10 way, includes hardware and angle adapter |
| General Specifications              |                                                                                  |
| Material                            | Stainless steel+PP                                                               |
| Block Color                         | Black                                                                            |
| Cables per hanger                   | 10                                                                               |
| Mounting                            | M8 threaded rod                                                                  |
| Dimensions                          |                                                                                  |
| Height                              | 36 mm   1.42 in                                                                  |
| Width                               | 40 mm   1.57 in                                                                  |
| Length                              | 205 mm   8.07 in                                                                 |
| Compatible Cable Jacket OD, maximum | 9.0 mm   0.35 in                                                                 |
| Compatible Cable Jacket OD, minimum | 7.0 mm   0.28 in                                                                 |
| Environmental Specifications        |                                                                                  |
| Operating Temperature               | -40 °C to +85 °C (-40 °F to +185 °F)                                             |
| UV Resistance                       | ≥720 hours, base on ISO4892.3-1994                                               |
| Salt Spray Test for Metal Parts     | ≥48 Hours, base on ISO 9227: 2017                                                |
| Packaging and Weights               |                                                                                  |
| Height, Packed                      | 300 mm   11.81 in                                                                |
| Width, Packed                       | 300 mm   11.81 in                                                                |
| UOM                                 | 1 Pcs                                                                            |
| Packaging                           | Bag                                                                              |
| Weight, Gross                       | 0.198 kg   0.437 lbs                                                             |
|                                     |                                                                                  |

For more information, please visit: www.maxdao.com

 $\boxtimes$ 

(in)

## ©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 27, 2024 Public



## **Certifications and Compliance**

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

RoHS

Compliant

For more information, please visit: www.maxdao.com



## ©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 27, 2024 Public Page 2 of 2