

## Cable Block Hanger, $\phi$ 10 Mounting Hole, Double Run, 19-35mm, With Outer Sawtooth Positioning

- Easy and quick installation
- Material for outdoor / indoor use
- The design of zigzag structure holds blocks in place when stacked
- The unique design can be adapted to more sizes of cables
- Patented product



### Product Classification

|                    |                                                                                                  |
|--------------------|--------------------------------------------------------------------------------------------------|
| Item Number        | 6008547                                                                                          |
| Part Number        | -                                                                                                |
| Detail Description | Cable block hanger, for 19-35 mm cable, $\phi$ 10 mounting hole, for 19-35 mm Cable, double runs |

### General Specifications

|                |                                           |
|----------------|-------------------------------------------|
| Block Material | 30% glass filled polypropylene            |
| Color          | Black                                     |
| Mounting       | Mounting hole for 3/8 or M10 threaded rod |

### Dimensions

|                                     |                    |
|-------------------------------------|--------------------|
| Height                              | 44.0 mm   1.73 in  |
| Width                               | 31.0 mm   1.23 in  |
| Length                              | 100.0 mm   3.94 in |
| Compatible Cable Jacket OD, maximum | 35.0 mm   1.38 in  |
| Compatible Cable Jacket OD, minimum | 19.0 mm   0.75 in  |

### Environmental Specifications

|                                   |                                          |
|-----------------------------------|------------------------------------------|
| Operating Temperature             | -40 °C to +85 °C (-40 °F to +185 °F)     |
| UV Resistance                     | $\geq$ 720 hours, base on ISO4892.3-1994 |
| Environmental Strength Capability | Double cable weight                      |

### Packaging and Weights

|                |                   |
|----------------|-------------------|
| Height, Packed | 32 mm   1.26 in   |
| Width, Packed  | 300 mm   11.81 in |
| Length, Packed | 310 mm   12.20 in |
| UOM            | Kit of 10         |
| Packaging      | Bag               |

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 23, 2024  
 Public

---

|                                                  |                                                                                |
|--------------------------------------------------|--------------------------------------------------------------------------------|
| Weight, Gross                                    | 1.20 kg   2.65 lb                                                              |
| <hr/> <b>Certifications and Compliance</b> <hr/> |                                                                                |
| ISO 9001:2015                                    | Designed, manufactured and/or distributed under this quality management system |
| RoHS                                             | Compliant                                                                      |

---

