

Hoisting Grip, Pre-Laced, for 1.20-1.38 in Cable

- Hoisting grips are used with safety ropes to safely lift cables onto the tower and providing permanent support
- Used for support to absorb additional strain from vibration, expansion, contraction and flexing.
- The pre-laced is used when top connector is installed after the antenna transmission line is hoisted.
- Stainless steel wire mesh is for indoor or outdoor use.
- CE certified



Product Classification

Material Number	6008554
Part Number	-
Detail Description	Hoisting Grip, Pre-Laced, for 1.20-1.38 in Cable

Details

Cable Range	1.20-1.38 in 30.5-35.0 mm
Mesh Length	24.0 in 609.6 mm
Eye Length	10.0 in 254.0mm
Maximum Spacing Intervals	200 ft 60.96 m
Approximate Break Strength	4000 lbs 1814 kg
Working Load	800 lbs 363 kg (Safety Factor 5*)
Mesh Material	Stainless Steel
Warning Label	Yellow Mylar

Packaging and Weights

UOM	1 pcs
Packaging	Bag
Weight, gross	0.38 lb 0.17 kg

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
CE	Compliant