

Heat Shrink Tube, single wall, ϕ 6mm, Clear

- High resistance to impact and abrasion
- Shrink ratio: 2:1
- Continuous operating temperature: -45°C to 125°C
- Shrink temperature: 70°C min



Product Classification

Item Number	6008585
Part Number	-
Detail Description	Heat Shrink Tube, single wall, ϕ 6mm, clear

General Specifications

Material	PE
Color	Clear
Cable Range	Φ 3.1-5.4 mm 0.13-0.21 in
Adhesive(Y/N)	N
Shrink Ratio	2:1

Dimensions

Expanded Inside Diameter, minimum	6 mm 0.23 in
Recovered Inside Diameter, maximum	3 mm 0.12 in
Total Recovered Wall Thickness	0.55 mm 0.021 in

Environmental Specifications

Operating Temperature	-45 °C to +125 °C (-49 °F to +257 °F)
Shrink Temperature Minimum	70 °C (94 °F)

Electrical Specifications

Voltage	600 V
Dielectric Strength	\geq 15 KV/mm

Packaging and Weights

Roll diameter	500 mm 1.64 in
Roll height	34 mm 0.11 in
Meter per roll	100 m
UOM	1 Pcs
Packaging	Carton

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 8, 2024

Public

Weight, Gross	0.92 kg 2.02 lbs
---------------	--------------------

Certifications and Compliance	
--------------------------------------	--

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
---------------	--

RoHS	Compliant
------	-----------

UL	Compliant
----	-----------

