


Hoisting Grip, Lace-up, for 2.99-3.01 in Cable

- Hoisting grips are used with safety ropes to safely lift cables onto the tower and providing permanent support
- Used for support to absorb additional strain from vibration, expansion, contraction and flexing.
- Use Lace-Up Grips for cable runs that are already terminated with connectors.
- Stainless steel wire mesh is for indoor or outdoor use.
- CE certified



Part Number-Detail DescriptionHoisting Grip, Lace-up, for 2.99-3.01 in CableDetailsCable Range2.99-3.01 in 75.9-76.6 mmMesh Length30.0 in 962.0 mmMesh Length30.0 in 457.2mmWeave Line Length98.4 in 2500 mmMaximum Spacing Intervals200 ft 60.96 mApproximate Break Strength7300 lbs 3311 kgWorking Load1460 lbs 662 kg (Safety Factor 5*)Mesh MaterialStainless SteelWarning LabelYellow MylarPackaging and Weights0.99 lb 0.45 kgWeight, gross0.99 lb 0.45 kgCertifications and ComplianceDesigned, manufactured and/or distributed under this quality management systemRos MaterialCompliant	Product Classification	
Detail DescriptionHoisting Grip, Lace-up, for 2.99-3.01 in CableDetailsCable Range2.99-3.01 in 75.9-76.6 mmMesh Length30.0 in 962.0 mmEye Length18.0 in 457.2mmWeave Line Length98.4 in 2500 mmMaximum Spacing Intervals200 ft 60.96 mApproximate Break Strength7300 lbs 3311 kgWorking Load1460 lbs 662 kg (Safety Factor 5*)Mesh MaterialStainless SteelWarning LabelYellow MylarPackaging and Weights1 pcsPackagingBagWeight, gross0.99 lb 0.45 kgCertifications and ComplianceDesigned, manufactured and/or distributed under this quality management systemRosCompliant	Material Number	6008745
Details Cable Range 2.99-3.01 in 75.9-76.6 mm Mesh Length 30.0 in 962.0 mm Eye Length 18.0 in 457.2mm Weave Line Length 98.4 in 2500 mm Maximum Spacing Intervals 200 ft 60.96 m Approximate Break Strength 7300 lbs 3311 kg Working Load 1460 lbs 662 kg (Safety Factor 5*) Mesh Material Stainless Steel Warning Label Yellow Mylar Packaging and Weights 1 pcs Packaging Bag Weight, gross 0.99 lb 0.45 kg Certifications and Compliance Designed, manufactured and/or distributed under this quality management system ROHS Compliant	Part Number	-
Cable Range2.99-3.01 in 75.9-76.6 mmMesh Length30.0 in 962.0 mmEye Length18.0 in 457.2mmWeave Line Length98.4 in 2500 mmMaximum Spacing Intervals200 ft 60.96 mApproximate Break Strength7300 lbs 3311 kgWorking Load1460 lbs 662 kg (Safety Factor 5*)Mesh MaterialStainless SteelWarning LabelYellow MylarPackaging and Weights1 pcsPackagingBagWeight, gross0.99 lb 0.45 kgCertifications and ComplianceDesigned, manufactured and/or distributed under this quality management systemRoHSCompliant	Detail Description	Hoisting Grip, Lace-up, for 2.99-3.01 in Cable
Mesh Length30.0 in 962.0 mmEye Length18.0 in 457.2mmWeave Line Length98.4 in 2500 mmMaximum Spacing Intervals200 ft 60.96 mApproximate Break Strength7300 lbs 3311 kgWorking Load1460 lbs 662 kg (Safety Factor 5*)Mesh MaterialStainless SteelWarning LabelYellow MylarPackaging and Weights1UOM1 pcsPackaging8agWeight, gross0.99 lb 0.45 kgCertifications and ComplianceJesigned, manufactured and/or distributed under this quality management systemRoHSCompliant	Details	
Eye Length18.0 in 457.2mmWeave Line Length98.4 in 2500 mmMaximum Spacing Intervals200 ft 60.96 mApproximate Break Strength7300 lbs 3311 kgWorking Load1460 lbs 662 kg (Safety Factor 5*)Mesh MaterialStainless SteelWarning LabelYellow MylarPackaging and WeightsUOM1 pcsPackagingBagWeight, gross0.99 lb 0.45 kgCertifications and ComplianceDesigned, manufactured and/or distributed under this quality management systemRoHSCompliant	Cable Range	2.99-3.01 in 75.9-76.6 mm
Weave Line Length98.4 in 2500 mmMaximum Spacing Intervals200 ft 60.96 mApproximate Break Strength7300 lbs 3311 kgWorking Load1460 lbs 662 kg (Safety Factor 5*)Mesh MaterialStainless SteelWarning LabelYellow MylarPackaging and Weights1 pcsPackagingBagWeight, gross0.99 lb 0.45 kgCertifications and ComplianceIso 9001:2015ISO 9001:2015Designed, manufactured and/or distributed under this quality management systemRoHSCompliant	Mesh Length	30.0 in 962.0 mm
Maximum Spacing Intervals200 ft 60.96 mApproximate Break Strength7300 lbs 3311 kgWorking Load1460 lbs 662 kg (Safety Factor 5*)Mesh MaterialStainless SteelWarning LabelYellow MylarPackaging and Weights1 pcsUOM1 pcsPackaging0.99 lb 0.45 kgWeight, gross0.99 lb 0.45 kgISO 9001:2015Designed, manufactured and/or distributed under this quality management systemRoHSCompliant	Eye Length	18.0 in 457.2mm
Approximate Break Strength7300 lbs 3311 kgWorking Load1460 lbs 662 kg (Safety Factor 5*)Mesh MaterialStainless SteelWarning LabelYellow MylarPackaging and Weights1 pcsUOM1 pcsPackagingBagWeight, gross0.99 lb 0.45 kgCertifications and ComplianceDesigned, manufactured and/or distributed under this quality management systemRoHSCompliant	Weave Line Length	98.4 in 2500 mm
Working Load1460 lbs 662 kg (Safety Factor 5*)Mesh MaterialStainless SteelWarning LabelYellow MylarPackaging and Weights1 pcsUOM1 pcsPackagingBagWeight, gross0.99 lb 0.45 kgCertifications and ComplianceISO 9001:2015Designed, manufactured and/or distributed under this quality management systemRoHSCompliant	Maximum Spacing Intervals	200 ft 60.96 m
Mesh Material Stainless Steel Warning Label Yellow Mylar Packaging and Weights 1 pcs UOM 1 pcs Packaging Bag Weight, gross 0.99 lb 0.45 kg Certifications and Compliance Designed, manufactured and/or distributed under this quality management system ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system RoHS Compliant	Approximate Break Strength	7300 lbs 3311 kg
Warning LabelYellow MylarPackaging and WeightsIUOM1 pcsPackagingBagWeight, gross0.99 lb 0.45 kgCertifications and ComplianceDesigned, manufactured and/or distributed under this quality management systemISO 9001:2015Designed, manufactured and/or distributed under this quality management systemRoHSCompliant	Working Load	1460 lbs 662 kg (Safety Factor 5*)
Packaging and Weights UOM 1 pcs Packaging Bag Weight, gross 0.99 lb 0.45 kg Certifications and Compliance Designed, manufactured and/or distributed under this quality management system ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system RoHS Compliant	Mesh Material	Stainless Steel
UOM1 pcsPackagingBagWeight, gross0.99 lb 0.45 kgCertifications and ComplianceISO 9001:2015Designed, manufactured and/or distributed under this quality management systemRoHSCompliant	Warning Label	Yellow Mylar
Packaging Bag Weight, gross 0.99 lb 0.45 kg Certifications and Compliance Designed, manufactured and/or distributed under this quality management system ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system RoHS Compliant	Packaging and Weights	
Weight, gross 0.99 lb 0.45 kg Certifications and Compliance Designed, manufactured and/or distributed under this quality management system ISO 9001:2015 Certifications and Compliance RoHS Compliant	UOM	1 pcs
Certifications and Compliance ISO 9001:2015 RoHS Designed, manufactured and/or distributed under this quality management system Compliant	Packaging	Bag
ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system Compliant	Weight, gross	0.99 lb 0.45 kg
ISO 9001:2015 quality management system RoHS Compliant	Certifications and Compliance	
	ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
CE Compliant	RoHS	Compliant
	CE	Compliant

For more information, please visit: www.maxdao.com

 \times

in

©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 22, 2024 Public