

## Cold Shrink Tube, $\phi$ 15x150mm, Black

- Suitable for 195, 200, 240, 400, 1/4" and 3/8" cable assemblies with TNC, NEX10, SMA, QMA connectors
- Used for GPS, Small Cell, Test & Measurement Jumpers Weatherproofing and Protection.



### Product Classification

Item Number	6008810
Part Number	-
Detail Description	Cold shrink tube, $\phi$ 15x150mm, black

### General Specifications

Material	Silicone
Cable type	Corrugated   Elliptical Waveguide   Smoothwall
Range	$\phi$ 4.9-15 mm   0.19-0.59 in
Color	Black
Mastic(Y/N)	N
Shrink Ratio	4:1

### Dimensions

Length Before Shrink	150 mm   6 in
Length After Shrink	165 mm   6.5 in
Inner Diameter Before Shrink(ID)	15 mm   0.6 in
Inner Diameter After Shrink(ID)	4.9 mm   0.19 in
Thickness After Shrink	2.5 mm   0.1 in

### Environmental Specifications

Operating Temperature	-60 °C to +90 °C (-76 °F to +194 °F)
Weatherproof Resistance	IP67, based on ISO20653:2013
UV Resistance	$\geq$ 1000 hours, base on ASTM G154-16

### Packaging and Weights

Height, Packed	200 mm   7.87 in
Width, Packed	75 mm   2.95 in
UOM	1 Pcs
Packaging	Bag

---

Weight, Gross	0.020 kg   0.044 lbs
---------------	----------------------

---

<b>Certifications and Compliance</b>	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

---

