

Certificate of Compliance

Certificate:	80191740	Master Contract:	304452
Project:	80191740	Date Issued:	2024-03-25
Issued to:	Jiangsu Maxdao Technology Limited Buliding 33 No.66. Meilan East Road Hailing Industrial Park TaiZhou, Jiangsu 225300 China		

Attention: Zhou Stark

The products listed below are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US' for Canada and US or with adjacent indicator 'US' for US only or without either indicator for Canada only.



Issued by: Amos Zheng Amos Zheng

PRODUCTS

C441201 OUTLET BOXES AND FITTINGS - Bushings, Fittings C441281 OUTLET BOXES AND FITTINGS - Bushings, Fittings - Certified to US Standards

Standard Duty Support Grip Single Eye Closed Mesh

Model(s)	Cable OD Range	Approximate Break Strength (lbs)	Safety Factor
SEHG1216	0.50-0.61"(12.7-15.5mm)	770 lbs.	10
SEHG1519	0.62-0.74"(15.7-18.8mm)	960 lbs.	10
SEHG1925	0.75-0.99"(19.1-25.1mm)	1300 lbs.	10
SEHG2532	1.00-1.24"(25.4-31.5mm)	1680 lbs.	10
SEHG3238	1.25-1.49"(31.8-37.8mm)	1680 lbs.	10
SEHG3844	1.50-1.74"(38.1-44.2mm)	1680 lbs.	10

QD-1397 Rev 2019-04-30



Certificate: 80191740

Project: 80191740

Master Contract: 304452

Date Issued: 2024-03-25

SEHG4450	1.75-1.99"(44.5-50.5mm)	2640 lbs.	10
SEHG5063	2.00-2.49"(50.8-63.2mm)	3760 lbs.	10
SEHG6375	2.50-2.99"(63.5-75.9mm)	3760 lbs.	10
SEHG7688	3.00-3.49"(76.2-88.6mm)	5040 lbs.	10
SEHG8899	3.50-3.99"(88.9-101.3mm)	5040 lbs.	10

Fiber Optic Support Grip Single Eye Closed Mesh

Model(s)	Cable OD Range	Approximate Break Strength (lbs)	Safety Factor
FOSG18	0.18-0.25"(4.57-6.35mm)	300 lbs.	10
FOSG22	0.22-0.32"(5.59-8.13mm)	300 lbs.	10
FOSG30	0.30-0.39"(7.62-9.91mm)	300 lbs.	10
FOSG37	0.37-0.48"(9.40-12.19mm)	300 lbs.	10
FOSG46	0.46-0.58"(11.68-14.73mm)	400 lbs.	10
FOSG56	0.56-0.71"(14.22-18.03mm)	500 lbs.	10
FOSG69	0.69-0.88"(17.53-22.35mm)	800 lbs.	10

Slack Pulling Grip Split Lace

Model(s)	Cable OD Range	Approximate Break Strength (lbs)	Safety Factor
LOSG022	0.75-0.99"(19.1-25.1mm)	3000 lbs.	5
LOSG025	1.00-1.24"(25.4-31.5mm)	4100 lbs.	5
LOSG032	1.25-1.49"(31.8-37.8mm)	4100 lbs.	5
LOSG038	1.50-1.74"(38.1-44.2mm)	5500 lbs.	5
LOSG042	1.75-1.99"(44.5-50.5mm)	7300 lbs.	5

APPLICABLE REQUIREMENTS

ANSI/UL 514B (Sixth Edition) - UL Standard for Safety Conduit, Tubing, and Cable Fittings

CSA C22.2 NO. 18.3:12 +Upd.1+Upd.2 (Second Edition) (R2022) - Conduit, tubing, and cable fittings



Certificate: 80191740

Project: 80191740

Master Contract: 304452 Date Issued: 2024-03-25

Notes:

Products certified under Class(es) C441201 have been certified under CSA's ISO/IEC 17065 accreditation with the Standards Council of Canada (SCC). <u>www.scc.ca</u>





Supplement to Certificate of Compliance

Certificate: 80191740

Master Contract: 304452

The products listed, including the latest revision described below, are eligible to be marked in accordance with the referenced Certificate.

Product Certification History

Project	Date	Description
80191740	2024-03-25	Original Certification for Standard Duty Support Grip Single Eye Closed Mesh, Cat. Nos. SEHG1216, SEHG1519, SEHG1925, SEHG2532, SEHG3238, SEHG3844, SEHG4450, SEHG5063, SEHG6375, SEHG7688, SEHG8899, Fiber Optic Support Grip Single Eye Closed Mesh, Cat. Nos. FOSG18, FOSG22, FOSG30, FOSG37, FOSG46, FOSG56, FOSG69, Slack Pulling Grip Split Lace, Cat. Nos. LOSG022, LOSG025, LOSG032, LOSG038, LOSG042. WMTC initial assessment to Yunuo Co., Ltd Lab.