PLATE# JTM0401 VERSION A/8 DATE 08/20/2024



Grounding Kit, Clip-on Type, 7/8", 0.6 Meter

- Easy and quick installation
- Low contact transition resistance of maximum
 10mO
- Operation temperature -40~70 °C
- Waterproof IP68



| Product Classification | | |
|-------------------------------|--|--|
| Item Number | 6001697 | |
| Part Number | - | |
| Detail Description | Grounding kit, clip-on type, for 7/8" cable, cable length 0.6m installation accessories included | |
| General Specifications | | |
| Bonding Conductor Material | Copper | |
| Bonding Conductor Wire Size | 6 AWG | |
| Grounding Strap Material | Copper | |
| Lug Type | One-hole lug | |
| Screw Material | Stainless Steel | |
| Flat washer Material | Stainless Steel | |
| Spring washer Material | Stainless Steel | |
| Nut Material | Stainless Steel | |
| Tape Material | PVC & Butyl | |
| Dimensions | | |
| Bonding Conductor Length | 0.6 m 2 feet | |
| Lug Hole Size | 8.4 mm 0.33 in | |
| Screw Size | M8 X 25 mm | |
| Suitable Cable | 7/8" | |
| Environmental Specifications | | |
| Operating Temperature | -40°C to +70 °C (-40 °F to +158 °F) | |
| Weatherproofing Method | Butyl and electric tape | |
| Electrical Specifications | | |
| Contact Transition Resistance | Maximum 10mΩ | |
| Packaging and Weights | | |

For more information, please visit: www.maxdao.com







| Height, Packed | 320 mm 12.60 in |
|-------------------------------|--|
| Width, Packed | 220 mm 8.66 in |
| Included | Grounding kit Hardware Lug One roll of PVC tape One roll of butyl rubber tape |
| иом | Kit |
| Packaging | Bag |
| Weight, Gross | 0.37 kg 0.82 lbs |
| Certifications and Compliance | |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |



www.maxdao.com

For more information, please visit: