## Strain Relief Grip, Deluxe Cord, M16, Straight Male, Cable Range 0.250-0.375 in,SS304

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL,CE certified

State State

Product Classification	
Part Number	-
Detail Description	Strain Relief Grip, Deluxe Cord, M16, Straight Male, Cable Range 0.250-0.375 in,SS304
Details	
Cable Range	0.250-0.375 in   6.35-9.53 mm
Thread Size	M16
Mesh Length	7.08 in   179.83 mm
Mesh Material	Stainless Steel
Body Material	Aluminum
Performance	
 Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting
Packaging and Weights	
Packaging Quantity	1 pcs
Weight, gross	0.101 lb   0.046 kg
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
CE	Compliant

For more information, please visit: www.maxdao.com

## ©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Sep 24, 2024 Public DATASHEET

UL

Compliant



For more information, please visit: www.maxdao.com

 $\square$ in

©Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Sep 24, 2024 Public

Page 2 of 2