

Grounding Kit, Universal Type, 1/4"-1-5/8", 0.5 Meter, Without Waterproof Kit

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation Temperature -40~70 °C
- Waterproof IP68



Product Classification	
Item Number	6003084
Part Number	-
Detail Description	Grounding Kit, universal type, for 1/4"-1-5/8" cable, 0.5 Meter, installation accessories included
General Specifications	
Bonding Conductor Material	Copper
Bonding Conductor Wire Size	AWG 6
Grounding Strap Material	Copper, Tin Plated
Lug Type	One-hole lug
Screw Material	Stainless Steel
- Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
Dimensions	
Bonding Conductor Length	0.5 m 1.7 feet
Lug Hole Size	M8
Screw Size	M8x25 mm
Suitable Cable	1/4"-1-5/8"
Environmental Specifications	
Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Electrical Specifications	
Contact Transition Resistance	Maximum 10mΩ
Packaging and Weights	
Height, Packed	320 mm 12.60 in
Width, Packed	220 mm 8.66 in

For more information, please visit: www.maxdao.com

 \boxtimes

(in

©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 21, 2024 Public

MAXDAO

DATASHEET

Included	Grounding kit Hardware Lug One Braided ground strap
UOM	Kit
Packaging	Bag
Weight, Gross	0.230 kg 0.507 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

Page 2 of 2

For more information, please visit: www.maxdao.com

Î \square

©Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 21, 2024 Public