


Copper Lug, 10mm² ,one hole M8, short barrel, without inspection window

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars
- Copper Tube Terminals between 6mm² & 800mm² have bell entry to ensure easy entry even for flexible conductors.
- The absence without inspection window prevents the entry of water or moisture into the crimped joint making these terminals suitable for outdoor applications.
- The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.



Product Classification	
Item Number	6003194
Part Number	-
Detail Description	Copper Lug, 10mm ² ,one hole M8, short barrel, without inspection window
General Specifications	
Material	Copper
Tongue Type	Standard
Tongue Angle	Straight
Surface	Tin-plated
Inspection Window	Without inspection window
Dimensions	
Bolt Size (E)	0.33 in 8.4 mm
Tang Width (C)	0.49 in 12.5 mm
Barrel length (B)	0.35 in 9.0 mm
Overall length (L)	1.06 in 27.0 mm
Inner diameter (d)	0.18 in 4.5 mm
Outer diameter (D)	0.24 in 6.1 mm

Electrical Specifications

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.
 The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
 Revised: Aug 30, 2024
 Public

Rating - Maximum Voltage 35KV

Environmental Specifications

Operating Temperature -40 °C to +90°C (-40 °F to +212 °F)

Storage Temperature -40 °C to +80 °C (-40 °F to +176 °F)

Packaging and Weights

Included Lug

Packaging Quantity and UOM 1 pcs

Piece Weight 0.01 lb | 0.005 kg

Certifications and Compliance

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

RoHS Compliant

