


Rotary Waveguide Cable Clamp, Rubber Lining Hole 32x18mm, For R100 Waveguide

- Easy and quick installation
- Robust design & material
- Universal fixing design on bracket, angle steel
- Operation Temperature -40~85 °C
- RoHS certified

**Product Classification**

Item Number	6003621
Part Number	-
Detail Description	Rotary waveguide cable clamp, rubber lining hole 25x15mm, for R100 waveguide

General Specifications

Metal Parts Material	Stainless steel 304
Finish	Passivation
Rubber Material	Natural Rubber
Rubber Color	Black
Applied Pole Size	40 - 150 mm 1.57 - 5.91 in
Waveguide Size	WR90 WG16 R100

Dimensions

Threaded Rod Length	400 mm 15.75 in
Rotary Adapter Width	45 mm 1.77 in
Round Member Adapter Width	12 mm 0.47 in
Rubber Lining Hole	32 mm X 18 mm 1.26 in X 0.71 in

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Corrosion Resistance	≥720 hours in salt spray chamber, base on IEC 60068-2-11
UV Resistance	≥720 hours, base on ISO4892.3-1994

Packaging and Weights

Height, Packed	600 mm 23.62 in
Width, Packed	200 mm 7.87 in
UOM	1 Pcs
Packaging	Bag

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 13, 2024
 Public

Weight, Gross	0.411 kg 0.906 lbs
---------------	----------------------

Certifications and Compliance	
--------------------------------------	--

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
---------------	--

RoHS	Compliant
------	-----------

