fin 🖂

Butt Splice , AWG 8#, long barrel, red

- Suitable for use in circuits rated 35KV or less, proper high voltage spacing and insulation techniques must be used
- Long barrel provides high pull-out force and increased retention for improved mechanical and electrical performance.
- Internal wire stops to prevent over-insertion of conductor.
- Seamless, high conductivity copper tubing for grounding and bonding applications
- "colour code" help choose the right connector, the colour name is also printed in order to avoid problems for those who are colour-blind.

Public



ΜΑΧΟΔΟ

Product Classification			
Item Number		6003856	
Part Number		-	
Detail Description		Butt Splice , AWG 8#, long barrel,red	
General Specifications			
Colour Code		Red	
Material		Copper	
Surface		Tin-plated	
Dimensions	L 		
Overall length (L)		2.00 in 50.8 mm	
Inner diameter (ID)		0.18 in 4.6 mm	
Outer diameter (OD)		0.27 in 6.9 mm	
Electrical Specifications			
Rating - Maximum Voltage		35KV	
Environmental Specificati	ons		
Operating Temperature		-40 °C to +90°C (-40 °F to +212 °F)	
Storage Temperature		-40 °C to +80 °C (-40 °F to +176 °F)	
For more information, please visit: www.maxdao.com	©Maxdao Inc. All rights reserved. The information contained herein is subject t changes or modify the contents of this docun Revised: Aug 30, 2024	o change without notice. We reserve the right to make technical nent without prior notice.	Page 1 of 2

DATASHEET



Packaging and Weights			
Included	Butt Splice		
Packaging Quantity and UOM	1 pcs		
Piece Weight	0.04 lb 0.02 kg		
Certifications and Compliance			
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system		
RoHS	Compliant		
UL	Compliant		

Page 2 of 2

For more information, please visit: www.maxdao.com

Î \boxtimes

©Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 30, 2024 Public