


**90° Copper Lug, AWG 2# , two hole 1/4", hole spacing 5/8", long barrel, without inspection window,brown**

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars
- Copper Tube Terminals between 6mm<sup>2</sup> & 800mm<sup>2</sup> have bell entry to ensure easy entry even for flexible conductors.
- The absence without inspection window prevents the entry of water or moisture into the crimped joint making these terminals suitable for outdoor applications.
- The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.
- "colour code" help choose the right connector, the colour name is also printed in order to avoid problems for those who are colour-blind.




**Product Classification**

Item Number	6003864
Part Number	-
Detail Description	90° Copper Lug, AWG 2# , two hole 1/4", hole spacing 5/8", long barrel, without inspection window,brown

**General Specifications**

Colour Code	Brown
Material	Copper
Tongue Type	Standard
Tongue Angle	90 degree
Surface	Tin-plated
Inspection Window	Without inspection window

**Dimensions**



Bolt Size	0.27 in   6.9 mm
Hole Spacing (H)	0.63 in   16.0 mm
Tang Width (C)	0.61 in   15.5 mm

For more information, please visit:  
www.maxdao.com



©Maxdao Inc. All rights reserved.  
The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.  
Revised: Aug 30, 2024  
Public

Barrel length (B)	1.38 in   35.1 mm
Overall length (L)	1.83 in   46.5 mm
Inner diameter (ID)	0.31 in   7.9 mm
Outer diameter(OD)	0.42 in   10.7 mm

**Electrical Specifications**

Rating - Maximum Voltage	35KV
--------------------------	------

**Environmental Specifications**

Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)

**Packaging and Weights**

Included	Lug
Packaging Quantity and UOM	1 pcs
Piece Weight	0.07 lb   0.03 kg

**Certifications and Compliance**

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant