


Heavy Quick Install Round Member Adapter, 50-150mm, SS304 Passivated

- Wider operating range
- For attaching to round members
- Good performance for outdoor



Product Classification

Item Number	6004364
Part Number	-
Detail Description	Quick install round member adapter, for 50-150mm round member, SS304 passivated

General Specifications

Material	Stainless steel 304
Surface Treatment	Passivation and sealing
Color	Natural
Screw Type	Slotted hex head

Dimensions

Length	590.0 mm 23.23 in
Band Width	14.0 mm 0.551 in
Band Thickness	0.6 mm 0.024 in
Size Range	50 - 150 mm 1.97 - 5.91 in

Mechanical Specifications

Minimum Destructive Torque	6.8 N·m
----------------------------	---------

Environmental Specifications

Corrosion Resistance	≥720 hours in salt spray chamber, base on IEC 60068-2-11
----------------------	--

Packaging and Weights

Height, Packed	220 mm 8.66 in
Width, Packed	320 mm 12.60 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.052 kg 0.115 lbs

Certifications and Compliance

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 23, 2024

Public

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 23, 2024

Public