

**Grounding Kit, Tinned GST Type, For TWS600 Cable, 0.93 Meter**

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation Temperature -40~70 °C
- Waterproof IP68
- Grounding cable meet UL certification

**Product Classification**

Item Number	6004735
Part Number	-
Detail Description	Grounding kit, tinned GST type, for TWS600 cable, 0.93 meter, installation accessories including

**General Specifications**

Bonding Conductor Material	Copper, Tin Plated
Bonding Conductor Wire Size	AWG 6
Grounding Strap Material	Copper, Tin Plated
Lug Type	Two-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
PVC tape Material	PVC
Butyl Rubber Tape Material	Butyl

**Dimensions**

Bonding Conductor Length	0.93 m   3.1 feet
Lug Hole Size	3/8"
Screw Size	3/8"x1"
Suitable Cable	TWS600

**Environmental Specifications**

Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Weatherproofing Method	Butyl and electric tape

**Electrical Specifications**

Contact Transition Resistance	Maximum 10mΩ
-------------------------------	--------------

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 21, 2024  
 Public

---

**Packaging and Weights**

---

Height, Packed	320 mm   12.60 in
Width, Packed	220 mm   8.66 in
Included	Grounding kit   Hardware   Lug   One roll of PVC tape   One roll of butyl rubber tape
UOM	Kit
Packaging	Bag
Weight, Gross	0.495 kg   1.091 lbs

---

**Certifications and Compliance**

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

---

