

Heat Shrink Tube, ϕ 180mm, Black, PE

- Covering and protecting bare splices or cable connections
- Various range of application



Product Classification

Item Number	6004862
Part Number	-
Detail Description	Heat shrink tube, ϕ 180mm x 25m, black

General Specifications

Material	PE
Color	Black
Shrink Ratio	\geq 2:1
Applied Cable Range	140 - 175 mm 5.51 - 6.89 in

Dimensions

Inner diameter Before Shrink	180.0 mm 7.09 in
Thickness Before Shrink	0.65 mm 0.026 in
Inner diameter After Shrink	90.0 mm 3.54 in
Thickness After Shrink	1.3 mm 0.05 in
Length	25.0 m 82 ft

Environmental Specifications

Continuous Operating Temperature	-45 °C to +125 °C (-67 °F to +257 °F)
Flammability	Compliant, base on UL224
Tensile Strength	\geq 10.4 Mpa, base on GB/T1408
Longitudinal Change	\leq 5%
Dielectric Strength	\geq 15KV/mm, base on GB/T1408

Packaging and Weights

Height, Packed	180 mm 7.09 in
Width, Packed	550 mm 21.65 in
Length, Packed	550 mm 21.65 in
UOM	1 Pcs

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 24, 2024
 Public

Packaging	Carton
Weight, Gross	11.8 kg 26.0 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

