

## Whipsock, Double Eye, Hose OD: 2.36-2.76 in, Galvanized Steel

- High-pressure hose safety restraint device, reliably stops the unpredictable and potentially hazardous movement of a high-pressure hose.
- Suited for applications where the media being transferred is under higher working pressures such as air, water, hydraulic, and slurry
- Prevent injuries or accidents resulting from hose or coupling failure.
- Two mounting points and the long gripping area
- CE certified



### Product Classification

|                    |   |
|--------------------|---|
| Item Number        | 6004998   |
| Part Number        | -   |
| Detail Description | Whipsock, Double Eye, Hose OD: 2.36-2.76 in, Galvanized Steel |

### Details

|                            |                                       |
|----------------------------|---------------------------------------|
| Cable Range                | 2.36-2.76 in   60.0-70.0 mm           |
| Mesh Length                | 35.0 in   889.0 mm                    |
| Eye Length                 | 9.0 in   228.6 mm                     |
| Approximate Break Strength | 13007 lbs   5900 kg                   |
| Working Load               | 2601 lbs   1180 kg (Safety Factor 5*) |
| Mesh Material              | Galvanized Steel                      |

### Packaging and Weights

|               |                     |
|---------------|---------------------|
| UOM           | 1 pcs               |
| Packaging     | Bag                 |
| Weight, gross | 1.613 lb   0.732 kg |

### Certifications and Compliance

|               |  |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS          | Compliant  |
| CE            | Compliant  |