

Grounding Kit, Clip-on Type, 1/2" S, 1 Meter

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation temperature -40~70 °C
- Waterproof IP68



Product Classification

Item Number	6005264
Part Number	-
Detail Description	Grounding kit, clip-on type, for 1/2" superflex cable, cable length 1.0m, installation accessories included

General Specifications

Bonding Conductor Material	Copper
Bonding Conductor Wire Size	6 AWG
Grounding Strap Material	Copper
Lug Type	One-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
Tape Material	PVC & Butyl

Dimensions

Bonding Conductor Length	1 m 39.4 in
Lug Hole Size	8.4 mm 0.33 in
Screw Size	M8 X 25 mm
Suitable Cable	1/2" S

Environmental Specifications

Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Weatherproofing Method	Butyl and electric tape

Electrical Specifications

Contact Transition Resistance	Maximum 10mΩ
-------------------------------	--------------

Packaging and Weights

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 26, 2024

Public

Height, Packed	320 mm 12.60 in
Width, Packed	220 mm 8.66 in
Included	Grounding kit Hardware Lug One roll of PVC tape One roll of butyl rubber tape
UOM	Kit
Packaging	Bag
Weight, Gross	0.308 kg 0.679 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

