## Copper Lug, AWG 12-10#, one hole 8#, Nylon-insulated, yellow

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars .
- Copper Terminals between 0.15mm2 & 240mm2 have bell entry to ensure easy entry even for flexible conductors.
- Internal barrel serrations assure good wire contact and maximum tensile strength.
- Brazed seam protects terminal barrel from splitting during the crimp process.
- "colour code" help choose the right connector.



Product Classification	
Item Number	6005610
Part Number	-
Detail Description	Copper Lug, AWG 12-10#, one hole 8#, Nylon-insulated,yellow
General Specifications	
Color Code	Yellow
Material	Copper
Tongue Type	Ring
Surface	Tin-plated
Bolt Size	0.17 in   4.3 mm
Tang Width (W)	0.37 in   9.5 mm
Barrel length (B)	0.56 in   14.1 mm
Overall length (L)	1.07 in   27.1 mm
Inner diameter (d)	0.14 in   3.5 mm
Outer diameter (D)	0.26 in   6.6 mm
Electrical Specifications	
Rating - Maximum Voltage	35KV
Environmental Specifications	
Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)

For more information, please visit: www.maxdao.com

 $\bowtie$ 

in

## ©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 30, 2024 Public



Page 1 of 2

TEMPLATE# ITM0401 VERSION A/8 DATE 08/20/2024

DATASHEET



## Storage Temperature -40 °C to +80 °C (-40 °F to +176 °F) Packaging and Weights Included

Packaging Quantity and UOM

Piece Weight

## **Certifications and Compliance**

ISO 9001:2015

RoHS

Designed, manufactured and/or distributed under this quality management system Compliant

Kit of 10

0.06 lb | 0.03 kg

TEMPLATE# ITM0401 VERSION A/8 DATE 08/20/2024

Page 2 of 2

For more information, please visit: www.maxdao.com

©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 30, 2024 Public