

## Copper Lug, AWG 2#Solid, one hole 3/8", long barrel, with inspection window,gray

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars
- Copper Tube Terminals between 6mm<sup>2</sup> & 800mm<sup>2</sup> have bell entry to ensure easy entry even for flexible conductors.
- Incorporates inspection window to check the correct cable positioning
- Long barrel provides high pull-out force and increased retention for improved mechanical and electrical performance.
- "colour code" help choose the right connector, the colour name is also printed in order to avoid problems for those who are colour-blind.




### Product Classification

Item Number	6006616
Part Number	-
Detail Description	Copper Lug, AWG 2#Solid, one hole 3/8", long barrel, with inspection window,gray

### General Specifications

Colour Code	Gray
Material	Copper
Tongue Type	Standard
Tongue Angle	Straight
Surface	Tin-plated
Inspection Window	With inspection window

### Dimensions



Bolt Size	3/8 in   10.2 mm
Tang Width (C)	0.60 in   15.5 mm
Barrel length (B)	1.12 in   29.2 mm
Overall length (L)	2.22 in   60.2 mm
Inner diameter (ID)	0.28 in   7.2 mm
Outer diameter (OD)	0.38 in   10.7 mm

### Electrical Specifications

For more information, please visit:  
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 30, 2024

Public

Rating - Maximum Voltage 35KV

---

**Environmental Specifications**

---

Operating Temperature -40 °C to +90°C (-40 °F to +212 °F)

Storage Temperature -40 °C to +80 °C (-40 °F to +176 °F)

---

**Packaging and Weights**

---

Included Lug

Packaging Quantity and UOM 1 pcs

Piece Weight 0.035 lb | 0.016 kg

---

**Certifications and Certificated**

---

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

RoHS Compliant

UL Compliant

