

## Hook Cable Clamp, M Type, 6x5-7mm+3x20-25mm

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C
- Hooking on round ø 8-25 and flat 3-25 mm



| Product Classification              |  |
|-------------------------------------|--|
| Item Number                         | 6007004  |
| Part Number                         | -  |
| Detail Description                  | Hook Cable Clamp for 6x5-7mm+3x20-25mm cable, hooking on round ø 8-25 and flat 3-25 mm |
| General Specifications              |  |
| Metal Material                      | Stainless steel 304  |
| Block Material                      | PA6  |
| Block Color                         | Black  |
| Cables Per Hanger                   | 6 X 5-7 mm+3 X 20-25 mm  |
| Dimensions                          |  |
| Height                              | 244.0 mm   9.61 in   |
|                                     | 55.6 mm   2.19 in  |
| Length                              | 45.0 mm   1.77 in  |
| Compatible Cable Jacket OD, maximum | 25.0 mm   0.98 in  |
| Compatible Cable Jacket OD, minimum | 5.0 mm   0.20 in   |
| Environmental Specifications        |  |
| Operating Temperature               | -40 °C to +85 °C (-40 °F to +185 °F)   |
| Corrosion Resistance                | $\geqslant$ 96 hours in salt spray chamber, base on ISO 9227:2017                      |
| UV Resistance                       | ≥720 hours, base on ISO4892.3-1994   |
| Vibration Test                      | ≥6Hours,base on IEC 60068-2-6-2007   |
| Packaging and Weights               |  |
| Height, Packed                      | 220 mm   8.66 in   |
| Width, Packed                       | 320 mm   12.60 in  |
| UOM                                 | 1 Pcs  |
| Packaging                           | Bag  |









| Weight, Gross                 | 0.291 kg   0.642 lbs   |
|-------------------------------|--|
| Certifications and Compliance |  |
| ISO 9001:2015                 | Designed, manufactured and/or distributed under this quality management system |
| RoHS                          | Compliant  |