

## Strain Relief Grip, Deluxe Cord, M25, Straight Male, Cable Range 0.625-0.750 in,SS304

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL,CE certified



### Classification

Item Number	6007132
Part Number	-
Detail Description	Strain Relief Grip, Deluxe Cord, M25, Straight Male, Cable Range 0.625-0.750 in,SS304,with O-Ring

### Details

Cable Range	0.625-0.750 in   15.88-19.05 mm
Thread Size	M25
Mesh Length	7.5 in   190.5 mm
Mesh Material	Stainless Steel
Body Material	Aluminum

### Performance

Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting

### Packaging and Weights

Packaging Quantity	1 kit
Weight, gross	0.2 lb   0.091 kg

### Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 24, 2024  
 Public

CE

Compliant

UL

Compliant

