

Heat Shrink Tube, ϕ 25mmx1.22m, Clear, EVA

- Covering and protecting bare splices or cable connections
- Various range of application
- UL certified



Product Classification

Item Number	6007312
Part Number	-
Detail Description	Heat shrink tube, ϕ 25mmx1.22m, Clear

General Specifications

Material	EVA
Color	Clear
Shrink Ratio	\geq 2:1
Applied Cable Range	12.8 - 24.0 mm 0.50 - 0.94 in

Dimensions

Inner diameter Before Shrink	26.0 mm 1.02 in
Thickness Before Shrink	0.45 mm 0.018 in
Inner diameter After Shrink	12.5 mm 0.49 in
Thickness After Shrink	0.90 mm 0.035 in
Length	1.22 m 48.0 in

Environmental Specifications

Continuous Operating Temperature	-55 °C to +125 °C (-67 °F to +257 °F)
Tensile Strength	\geq 10.4 Mpa, base on GB/T1408
Longitudinal Change	\leq 5%
Dielectric Strength	\geq 15KV/mm, base on GB/T1408

Packaging and Weights

Height, Packed	185 mm 7.28 in
Width, Packed	1400 mm 55.12 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.045 kg 0.099 lbs

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 24, 2024

Public

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant

