

Whipcheck, Hose To Hose, 8 in Hose Size,Stainless Steel

- Whipchecks are commonly used on hose for air, water blast, drilling, steam, concrete, sandblast or other high pressure applications
- Whipchecks should be installed in the fully extended position (no slack) for proper safety assurance
- Hose to hose restraints is slipped over the hose on each side of the fitting and prevent hose whip in the event of fitting separation or failure
- CE certified



Product Classification

| | |
|--------------------|---|
| Material Number | 6007513 |
| Part Number | - |
| Detail Description | Whipcheck, Hose To Hose, 8 in Hose Size,Stainless Steel |

Details

| | |
|----------------------------|---------------------------------------|
| Cable Range | 8.0 in 203.2 mm |
| Length | 55.0 in 1400 mm |
| Max. Working Pressure | 200 psi |
| Approximate Break Strength | 33000 lbs 15000 kg |
| Working Load | 6600 lbs 2993 kg (Safety Factor 5*) |
| Mesh Material | Stainless Steel |

Packaging and Weights

| | |
|---------------|-------------------|
| UOM | 1 pcs |
| Packaging | Bag |
| Weight, gross | 1.76 lb 0.80 kg |

Certifications and Compliance

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |
| CE | Compliant |

