
ΜΑΧΟΔΟ

Butt Splice, AWG 1#, long barrel, green

- Suitable for use in circuits rated 35KV or less, proper high voltage spacing and insulation techniques must be used
- Long barrel provides high pull-out force and increased retention for improved mechanical and electrical performance.
- Internal wire stops to prevent over-insertion of conductor.
- Seamless, high conductivity copper tubing for grounding and bonding applications
- "colour code" help choose the right connector, the colour name is also printed in order to avoid problems for those who are colour-blind.



| Product Classification | |
|------------------------------|---|
| Item Number | 6007826 |
| Part Number | - |
| Detail Description | Butt Splice , AWG 1#, long barrel,green |
| General Specifications | |
| Colour Code | Green |
| Material | Copper |
| Surface | Tin-plated |
| | |
| Overall length (L) | 3.07 in 78.0 mm |
| Inner diameter (ID) | 0.36 in 9.1 mm |
| Outer diameter (OD) | 0.47 in 11.7 mm |
| Electrical Specifications | |
| Rating - Maximum Voltage | 35KV |
| Environmental Specifications | |
| Operating Temperature | -40 °C to +90°C (-40 °F to +212 °F) |

TEMPLATE# ITM0401 VERSION A/8 DATE 08/20/2024



| Storage Temperature | -40 °C to +80 °C (-40 °F to +176 °F) |
|-------------------------------|--|
| Packaging and Weights | |
| Included | Butt Splice |
| Packaging Quantity and UOM | 1 pcs |
| Piece Weight | 0.07 lb 0.03 kg |
| Certifications and Compliance | |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |
| UL | Compliant |

Page 2 of 2



www.maxdao.com

For more information, please visit:

Public