## ΜΑΧΟΔΟ

## Butt Splice, AWG 2/0#, long barrel, black

- Suitable for use in circuits rated 35KV or less, proper high voltage spacing and insulation techniques must be used
- Long barrel provides high pull-out force and increased retention for improved mechanical and electrical performance.
- Internal wire stops to prevent over-insertion of conductor.
- Seamless, high conductivity copper tubing for grounding and bonding applications
- "colour code" help choose the right connector, the colour name is also printed in order to avoid problems for those who are colour-blind.



Product Classification		
Item Number		6007828
Part Number		-
Detail Description		Butt Splice , AWG 2/0#, long barrel,black
General Specifications		
Colour Code		Black
Material		Copper
Surface		Tin-plated
	L	
Overall length (L)		3.30 in   83.8 mm
Inner diameter (ID)		0.45 in   11.4 mm
Outer diameter (OD)		0.56 in   14.2 mm
Electrical Specifications		
Rating - Maximum Voltage		35KV
Environmental Specifications		
Operating Temperature		-40 °C to +90°C (-40 °F to +212 °F)





Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Packaging and Weights	
Included	Butt Splice
Packaging Quantity and UOM	1 pcs
Piece Weight	0.07 lb   0.03 kg
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant

Page 2 of 2



www.maxdao.com

For more information, please visit:

Public