

Feeder Cable Clamp, 2x7/8", Q235 Plated Dacromet, Without U Clamp

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C



Product Classification

Item Number	6007857
Part Number	-
Detail Description	Feeder cable clamp, for 2x7/8 in cable, 2 way, includes hardware, without angle adapter

General Specifications

Metal Material	Galvanized steel
Finish	Dacromet
Metal Color	Sliver
Block Material	PP
Block Color	Black
Cables Per Hanger	2
Mounting	M8 hardware

Dimensions

Height	36.0 mm 1.42 in
Width	83.2 mm 3.28 in
Length	90.0 mm 3.54 in
Compatible Cable Jacket OD, maximum	29.0 mm 1.14 in
Compatible Cable Jacket OD, minimum	27.0 mm 1.06 in
Normal Size	7/8 in

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Corrosion Resistance	≥120 hours in salt spray chamber, base on ISO 9227: 2017
UV Resistance	≥720 hours, base on ISO4892.3-1994
Environmental Strength Capability	Double cable weight

Packaging and Weights

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 5, 2024

Public

Height, Packed	320 mm 12.60 in
Width, Packed	220 mm 8.66 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.074 kg 0.163 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

