

Strain Relief Grip, Deluxe Cord,PG29,Straight Male,Cable Range 0.56-0.69 in, SS304

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL, CE certified



Product Classification

Material Number	6007980
Part Number	-
Detail Description	Strain Relief Grip, Deluxe Cord,PG29,Straight Male,Cable Range 0.56-0.69 in, SS304

Details

Cable Range	0.56-0.69 in 14.2-17.5 mm
Thread Size	PG29
Mesh Length	7.5 in 190.5 mm
Approximate Break Strength	550 lbs 249 kg
Mesh Material	Stainless Steel
Ring Material	Aluminum Alloy

Performance

Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting

Packaging and Weights

UOM	1 pcs
Packaging	Bag
Weight, gross	0.68 lb 0.28 kg

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this
---------------	--

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 30, 2024
Public

RoHS

CE

UL

quality management system

Compliant

Compliant

Compliant

