

Strain Relief Grip, Deluxe Cord, PG36, Straight Male, Cable Range 0.88-1.00 in, SS304

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL, CE certified



Product Classification		
Material Number	6007981	
Part Number	-	
Detail Description	Strain Relief Grip, Deluxe Cord,PG36,Straight Male,Cable Range 0.88-1.00 in,SS304	
Details		
Cable Range	0.88-1.00 in 22.4-25.4 mm	
Thread Size	PG36	
Mesh Length	8.5 in 209.5 mm	
Approximate Break Strength	450 lbs 204 kg	
Mesh Material	Stainless Steel	
Ring Material	Aluminum Alloy	
Performance		
	UL 94HB & UL 94V-2	
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2	
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)	
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting	
Packaging and Weights		
UOM	1 pcs	
Packaging	Bag	
Weight, gross	0.66 lb 0.30 kg	
Certifications and Compliance		

ISO 9001:2015

 \times

5

Designed, manufactured and/or distributed under this

For more information, please visit: www.maxdao.com

©Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 30, 2024 Public



	quality management system
RoHS	Compliant
CE	Compliant
UL	Compliant

For more information, please visit: www.maxdao.com



©Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 30, 2024 Public

Page 2 of 2