
TEMPLATE# ITM0401 VERSION A/8 DATE 08/20/2024



Strain Relief Grip, Deluxe Cord, PG36, Straight Male, Cable Range 0.75-0.88 in, SS304

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- **UL**, CE certified



| Product Classification | |
|-------------------------------|--|
| Material Number | 6007985 |
| Part Number | - |
| Detail Description | Strain Relief Grip, Deluxe Cord,PG36,Straight Male,Cable Range 0.75-0.88 in,SS304 |
| Details | |
| Cable Range | 0.75-0.88 in 19.1-22.4 mm |
| Thread Size | PG36 |
| Mesh Length | 9.0 in 228.6 mm |
| Approximate Break Strength | 500 lbs 226 kg |
| Mesh Material | Stainless Steel |
| Ring Material | Aluminum Alloy |
| Performance | |
| Flammability | UL 94HB & UL 94V-2 |
| Hazardous Locations | Suitable for use in hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |
| Operating Temperatures | -34 °C to +115 °C (-30 °F to +240 °F) |
| Wet Locations | Suitable for use in wet locations when used with a listed sealing ring between box and fitting |
| Packaging and Weights | |
| UOM | 1 pcs |
| Packaging | Bag |
| Weight, gross | 0.66 lb 0.30 kg |
| Certifications and Compliance | |

Designed, manufactured and/or distributed under this





www.maxdao.com

ISO 9001:2015

For more information, please visit:



quality management system

RoHS Compliant

CE Compliant

UL Compliant

