

Strain Relief Grip, Deluxe Cord,NPT1-1/4,90° Male,Cable Range 0.75-0.88 in, SS304

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL, CE certified



Product Classification

| | |
|--------------------|---|
| Item Number | 6008112 |
| Part Number | - |
| Detail Description | Strain Relief Grip, Deluxe Cord,NPT1-1/4,90° Male,Cable Range 0.75-0.88 in, SS304 |

Details

| | |
|----------------------------|-----------------------------|
| Cable Range | 0.75-0.88 in 19.1-22.4 mm |
| Thread Size | NPT1-1/4 |
| Mesh Length | 9.0 in 228.6 mm |
| Approximate Break Strength | 1100 lbs 498 kg |
| Mesh Material | Stainless Steel |
| Ring Material | Aluminum Alloy |

Performance

| | |
|------------------------|--|
| Flammability | UL 94HB & UL 94V-2 |
| Hazardous Locations | Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |
| Operating Temperatures | -34 °C to +115 °C (-30 °F to +240 °F) |
| Wet Locations | Suitable for use in wet locations when used with a listed sealing ring between box and fitting |

Packaging and Weights

| | |
|---------------|-------------------|
| UOM | 1 pcs |
| Packaging | Bag |
| Weight, gross | 0.62 lb 0.28 kg |

Certifications and Compliance

ISO 9001:2015 Designed, manufactured and/or distributed under this

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.
The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
Revised: Aug 30, 2024
Public

RoHS

CE

UL

quality management system

Compliant

Compliant

Compliant

