

Radiating Clamp, 1-5/8", PA6

- Easy and quick installation
- Robust design & material for outdoor / indoor use
- Operation Temperature -40~85 °C.



reral Specifications PA6, PA6, Black es Per Hanger 1 X 1 Inting Hole 8.4 m Rensions Inting Hole 25.0	226 ating clamp for 1-5/8 in radiating cable
reral Specifications PA6, r Black es Per Hanger 1 X 1 Inting Hole 8.4 m Rensions Inting Hole 73.2 Inting Hole 25.0	ating clamp for 1-5/8 in radiating cable
reral Specifications PA6, PA6, Black es Per Hanger 1 X 1 Inting Hole 8.4 m Rensions Inting Hole 25.0	ating clamp for 1-5/8 in radiating cable
erial PA6, r Black es Per Hanger 1 X 1 Inting Hole 8.4 m ensions tht 73.2 th 25.0	
r Black es Per Hanger 1 X 1 inting Hole 8.4 m ensions tht 73.2 th 25.0	
es Per Hanger 1 X 1 Inting Hole 8.4 m Internations Inting Hole 73.2 In The Property of the International Internati	Low Smoke Zero Halogen
nting Hole 8.4 n nensions tht 73.2 th 25.0	K
ht 73.2 th 25.0	-5/8"
ht 73.2 th 25.0	nm 0.33 in
th 25.0	
	mm 2.88 in
9th 55.5	mm 0.98 in
	mm 2.19 in
mal Size 1-5/8	3 in
ger Spacing, maximum 1.0 n	n 3.28 ft
ironmental Specifications	
rating Temperature -40 °	C to +85 °C (-40 °F to +185 °F)
nmability UL94	I V-0
Resistance ≥10	00 hours, base on ISO4892.3-1994
kaging and Weights	
ht, Packed 300 r	mm 11.81 in
rh, Packed 500 r	mm 19.69 in
// Kit o	 f 10
aging Bag	I IU
ght, Gross 0.265	110

Certifications and Compliance









ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

