MAXDAO

Copper Lug, AWG 10#, one hole M4, short barrel, without inspection window

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars
- Copper Tube Terminals between 6mm2 & 800mm2 have bell entry to ensure easy entry even for flexible conductors.
- The absence without inspection window prevents the entry of water or moisture into the crimped joint making these terminals suitable for outdoor applications.
- The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.



Product Classification	
Item Number	6008277
Part Number	-
Detail Description	Copper Lug, AWG 10#, one hole M4, short barrel,without inspection window
General Specifications	
Material	Copper
Tongue Type	Standard
Tongue Angle	Straight
Surface	Tin-plated
Inspection Window	Without inspection window

O OE	B
	L L

Bolt Size (E)	0.17 in 4.3 mm
Tang Width (C)	0.33 in 8.5 mm
Barrel length (B)	0.35 in 9.0 mm
Overall length (L)	0.91 in 23.0 mm
Inner diameter (d)	0.14 in 3.5 mm
Outer diameter (D)	0.26 in 6.5 mm

Electrical Specifications

For more information, please visit: www.maxdao.com



Dimensions

TEMPLATE# ITM0401 VERSION A/8 DATE 08/20/2024



Rating - Maximum Voltage	35KV
Environmental Specifications	
Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Packaging and Weights	
Included	Lug
Packaging Quantity and UOM	1 pcs
Piece Weight	0.02 lb 0.008 kg
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

