

## Cold Shrink Tube, $\phi 70 \times 275 \text{mm}$ , Black

- Easy and quick installation
- Manufactured by EPDM rubber
- Suitable for a wide range of cable sizes
- No special tools or training required for installation
- Offering good mechanical, insulation and sealing protection



### Product Classification

Item Number	6008318
Part Number	-
Detail Description	Cold shrink tube, $\phi 70 \times 275 \text{mm}$ , for 1-5/8 in or 1-1/4 in to 1/4 in through 1/2 in connections, EVA tape included

### General Specifications

Cold shrink tube Material	EPDM
Tape Material	EVA
Cable type	Corrugated   Elliptical Waveguide   Smoothwall
Cable Range	$\phi 7.37 - 30.48 \text{ mm}$   0.29 - 1.20 in
Color	Black
Mastic(Y/N)	N

### Dimensions

Length Before Shrink	275 mm   10.83 in
Length After Shrink	305 mm   12.0 in
Inner Diameter Before Shrink(ID)	69.85 mm   2.75 in
Inner Diameter After Shrink(ID)	22.0 mm   0.87 in
Thickness After Shrink	3.5 mm   0.138 in

### Environmental Specifications

Operating Temperature	-60 °C to +90 °C (-76 °F to +194 °F)
Weatherproof Resistance	IP67, based on ISO20653:2013
UV Resistance	$\geq 1000$ hours, base on ASTM G154-16

### Packaging and Weights

Height, Packed	80 mm   3.15 in
Width, Packed	80 mm   3.15 in
Length, Packed	310 mm   12.20 in

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 24, 2024

Public

Included	One cold shrink tube   Two EVA tape   One installation guide
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.294 kg   0.648 lbs
<b>Certifications and Compliance</b>	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

