

Jumper Cable, 4.3-10 Male to 4.3-10 Male, 1/2" Superflexible Cable, 3 Meter

- Stable premium VSWR, outstanding and consistent inter modulation performance
- Improves network performance, reduces the number of dropped calls and avoids revenue loss
- RoHS certified



Product Classification

Item Number	6008321
Part Number	-
Detail Description	Jumper cable, 4.3-10 Male to 4.3-10 Male, 1/2" Superflexible Cable, 3 Meter

General Specifications

Connector 1 Type	4.3-10 male
Connector 2 Type	4.3-10 male
Cable Type	1/2" Superflexible Cable

Dimensions

Length	3 Meter
--------	---------

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Waterproof	IP68, IEC 60529

Electrical Specifications

Characteristic Impedance	50 ohm
Frequency Range	DC-3GHz
VSWR	≤ 1.15(DC-3GHz)
PIM3	≤ -160dBc
Mating Cycles	≥ 500

Packaging and Weights

Height, Packed	400 mm 15.74 in
Width, Packed	400 mm 15.74 in
UOM	Pcs
Packaging	Bag
Weight, Gross	0.521 kg 1.148 lbs

Certifications and Compliance

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 2, 2024
 Public

Page 1 of 2

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

