

### Copper Lug, AWG 6#, one hole 3/8", Nylon-insulated,blue

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars .
- Copper Terminals between 0.15mm<sup>2</sup> & 240mm<sup>2</sup> have bell entry to ensure easy entry even for flexible conductors.
- Internal barrel serrations assure good wire contact and maximum tensile strength.
- Brazed seam protects terminal barrel from splitting during the crimp process.
- "colour code" help choose the right connector.




#### Product Classification

Item Number	6008342
Part Number	-
Detail Description	Copper Lug, AWG 6#, one hole 3/8", Nylon-insulated,blue

#### General Specifications

Color Code	Blue
Material	Copper
Tongue Type	Ring
Surface	Tin-plated

#### Dimensions



Bolt Size	0.41 in   10.5 mm
Tang Width (W)	0.71 in   18.0 mm
Barrel length (B)	0.91 in   23.0 mm
Overall length (L)	1.77 in   45.0 mm
Inner diameter (d)	0.23 in   5.9 mm
Outer diameter (D)	0.38 in   9.7 mm

#### Electrical Specifications

Rating - Maximum Voltage	35KV
--------------------------	------

#### Environmental Specifications

Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
-----------------------	-------------------------------------

For more information, please visit:  
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 30, 2024  
Public

Storage Temperature -40 °C to +80 °C (-40 °F to +176 °F)

---

**Packaging and Weights**

---

Included Lug  
Packaging Quantity and UOM Kit of 10  
Piece Weight 0.06 lb | 0.03 kg

---

**Certifications and Compliance**

---

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system  
RoHS Compliant

