

Strain Relief Grip, Dust Tight, NPT1/2", Straight Male, Cable Range 0.30-0.43 in, Galvanized Steel

- For indoor use in wiring of enclosures, power boxes, machine tools, power centers and bus drop systems
- Prevents severe cable bending and pull-out
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Easy installation
- UL, CE certified



Product Classification

Item Number	6008432
Part Number	-
Detail Description	Strain Relief Grip, Dust Tight, NPT1/2", Straight Male, Cable Range 0.30-0.43 in, Galvanized Steel

Details

Cable Range	0.30-0.43 in 7.6-10.9 mm
Thread Size	NPT 1/2
Mesh Length	4.5 in 114.3 mm
Approximate Break Strength	150 lbs 68 kg
Mesh Material	Galvanized Steel
Ring Material	Aluminum Alloy

Performance

Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2

Packaging and Weights

UOM	1 pcs
Packaging	Bag
Weight, gross	0.11 lb 0.05 kg

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 30, 2024
 Public

CE

Compliant

UL

Compliant

